vizulo
SUNFLOWER
CE RoHS

V	220 - 240
Hz	50
W	20 - 100
lm	880 - 11000
lm/W	up to 11 lm/W
K	3000 / 4000
°C	+10 to +35
CRI	>80

Chromaticity tolerance (initial MacAdam): 3
DALI / Non dimmable
Mounting: Surface / Suspended
Body material: Aluminium profile, steel sheet
Body color: White RAL 9016, Grey
Cover type: Prismatic / Opal
Warranty 3 - 5 years
50 000 h (L90B50) at Ta = 25 °C
100 000 h (L80B50) at Ta = 25 °C

RoHS
IP20

Total lumen output for final product can differ from typical data by 7% due to special conditions of LED manufacturing processes.

Last modified | **2019, 2 October**
Data subject to change

Dimensions

Optic

Opal

Microprismatic

Model name principles

SF

Power [W]	008 ... 100
Color rendering index	≥80 - 8 ≥90 - 9
Color temperature [K] Standard values:	3000 K - 30 4000 K - 40
Mounting	suspended - S surface - F
Shape	round - R
Size [mm]	060...120
Color	white - W grey - G
Cover	opal - O microprismatic - P
LED modules	standard - 1
Dimming	non dimmable - N DALI - D
Emergency	no emergency - 0 1 hour - 1 3 hours - 3
Insulation class	Class I - 1

VIZULO

Starta street 1
Riga, LV – 1026, Latvia

Sales: + 371 67 383 023
Production: + 371 67 383 024

office@vizulo.com
www. vizulo.com

VIZULO

VIZULO_PHOTO