

MIDPOINT SURFACE | A6



DE LED-Anbaustrahler für Deckenmontage. 350° drehbar und 90° schwenkbar. Konverter im Strahlerkopf integriert, einfach schaltbar. LED Engine wahlweise XICATO ARTIST für höchste Lichtqualität mit bester Farbwiedergabe und 5 Jahre Garantie für Farbkonstanz (MacAdams3) oder ECO für höchste Energieeffizienz bei optimalem Preis-Leistungsverhältnis und CRI>90. Farbtemperaturen 2700K, 3000K oder 4000K. Austauschbare Linsen-Reflektoroptiken mit sphärischer Facettenoptik. Ausstrahlwinkel: 10° (Spot), 20° (Medium), 35° (Flood) oder 50° (Wide Flood).

EN LED surface-mounted spotlight for ceilings. 350° rotatable and 90° tiltable. Driver integrated into spotlight head, switchable. LED Engine with XICATO ARTIST for highest light quality and colour rendering, including 5 year warranty for colour consistency (Mac Adams 3). Alternatively ECO for highest energy efficiency with optimal price-performance ratio and CRI> 90. Colour temperature 2700K, 3000K or 4000K. Replaceable lens reflector optics with spherical faceted optics. Beam angle: 10° (Spot), 20° (Medium), 35° (Flood) oder 50° (Wide Flood).

FR Projecteur apparent/saillie pour montage en plafonnier. Orientable à 350° et pivotant à 90°. Driver intégré dans la tête du projecteur, ON/OFF. Module/COB LED XICATO ARTIST en option pour une qualité d'éclairage maximale et un rendu des couleurs exceptionnel + 5 ans de garantie sur le niveau des couleurs (MacAdams 3) ou ECO pour une efficacité énergétique et un rapport qualité-prix optimal + IRC supérieur à 90 inclus. Température de couleur 2700K, 3000K ou 4000K. Réflecteur avec optique de lentille interchangeable et facettes de réflexion sphérique. Angle d'ouverture/faisceau: 10° (Spot), 20° (Medium), 35° (Flood) oder 50° (Wide Flood).



PRODUCT-CODE:		P	A	B	S	E	-	9	2	7	F	M	-	B	K
PRODUCT FAMILY	-	P: Midpoint													
TYPE	-	A6: Surface mounted tiltable													
BEAM ANGLE	-	A: Spot 10°, B: Medium 20°, C: Flood 35°, D: Wide Flood 50°													
SURFACE FINISH	-	W: Snow White, V: Ivory White, S: Radiant Silver, B: Jet Black, H: Champagne Silver													
CONTROL GEAR	-	E: On/Off, X: Integrated Dimmer, L: DALI													
COLOUR RENDER	-	9: CRI>90													
COLOUR TEMP.	-	27: 2700K, 30: 3000K, 40: 4000K													
LED-ENGINE	-	F: Eco [Ra> 90], A: Artist [Ra> 97, Xicato]													
POWER	-	E: Low Power M: Medium Power													
OPTIC RING	-	W: Snow White, V: Ivory White, S: Radiant Silver, B: Jet Black, H: Champagne Silver, G: Satin Gold, K: Satin Copper													
COVER	-	K: Clear Cover [Standard], P: Prismatic Lens, H: Honeycomb Louver, B: Dichroic Filter [Bread], M: Dichroic Filter [Meat]													



SPOT 10° LED ENGINE ECO, MEDIUM POWER

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	25250/12700	0.24 m
2 m	6312/3175	0.48 m
3 m	2806/1411	0.72 m
4 m	1578/794	0.95 m

LED Engine	2700K	3000K	4000K
Eco Low Power [20W]	1230	1350	1440
Eco Medium Power [31W]	1660	1860	2020
Artist Low Power [21W]	1040	1090	1190
Artist Medium Power [33W]	1400	1480	1560

MEDIUM 20° LED ENGINE ECO, MEDIUM POWER

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	17447/8455	0.32 m
2 m	4362/2114	0.64 m
3 m	1939/939	0.96 m
4 m	1090/528	1.30 m

LED Engine	2700K	3000K	4000K
Eco Low Power [20W]	1580	1740	1850
Eco Medium Power [31W]	2360	2640	2870
Artist Low Power [21W]	1330	1390	1510
Artist Medium Power [33W]	1980	2110	2220

FLOOD 35° LED ENGINE ECO, MEDIUM POWER

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	6251/2731	0.63 m
2 m	1563/683	1.30 m
3 m	695/303	1.90 m
4 m	391/171	2.50 m

LED Engine	2700K	3000K	4000K
Eco Low Power [20W]	1530	1680	1790
Eco Medium Power [31W]	2280	2550	2780
Artist Low Power [21W]	1290	1350	1470
Artist Medium Power [33W]	1930	2060	2160

WIDE FLOOD 50° LED ENGINE ECO, MEDIUM POWER

Mounting Height	Illuminance [Lux] center/side	Beam Diameter
1 m	3550/1319	0.94 m
2 m	887/330	1.90 m
3 m	394/147	2.80 m
4 m	222/82	3.80 m

LED Engine	2700K	3000K	4000K
Eco Low Power [20W]	1440	1580	1680
Eco Medium Power [31W]	2230	2490	2710
Artist Low Power [21W]	1250	1310	1430
Artist Medium Power [33W]	1910	2040	2140

