

BOOTES LED1X800 E756 T840 OP LT80 • 1020216



Product:	Bootes LED1x800 E756 T840 OP LT80
Order code:	1020216
Family:	Bootes LED
Product group:	Surface and suspended luminaires

GENERAL DATA

Description:	Surface mounted decorative LED luminaire Light distribution type: direct Diffuser: opal diffuser, PMMA Housing: steel Colour: grey (RAL 9006)
Installation:	On the ceiling. Push-in terminal, 3x2x2.5mm ²
Environment	Indoor
Application	office, education, corridor, retail, public place, hotel, staircase, bathroom

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	9
Power factor:	>0,95	Control gear:	ECG on/off
Connection:	Push-in terminal, 3x2x2.5mm ²		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm (ta+25°C):	779	System efficacy, lm/W:	89
CRI (Ra):	80+	CCT, K:	4000
LED lifetime, h:	75000/L80B50	Ripple current (≤120 Hz), %:	≤3


TECHNICAL DATA

Net weight, kg:	1.9	Quantity in package, pcs:	1
Packaging volume, m³/pcs:	0.01339464	Pallet quantity, pcs:	60
Dimensions, mm:	382x382x75		

STANDARDS


Operating temperature range, °C:	ta 0...+35	Protection class IEC:	I
Ingress protection code:	IP44	Mechanical impact resistance:	IK02
EEC:	A+	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



W, mm	L, mm	H, mm	A, mm	B, mm	C, mm	D, mm
632	632	75	520	520	286	49
382	382	65	270	270	96	49
382	1132	75	781	281	45	275
882	882	75	772	772	687	45

Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2021-11-24 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org